

Package: wideRhino (via r-universe)

May 15, 2026

Title High-Dimensional Methods via Generalised Singular Decomposition

Version 1.1.0

Description Construct a Canonical Variate Analysis Biplot via the Generalised Singular Value Decomposition, for cases when the number of samples is less than the number of variables. For more information on these biplots, see Ganey, R., & Gardner-Lubbe, S. (2026) <[doi:10.1007/s10260-025-00831-y](https://doi.org/10.1007/s10260-025-00831-y)>.

License MIT + file LICENSE

Encoding UTF-8

Roxygen list(markdown = TRUE)

Depends R (>= 4.1.0)

Imports geigen, Matrix, MASS, ggplot2, dplyr

Suggests knitr, rmarkdown, testthat

Config/Needs/website rmarkdown

Config/roxygen2/version 8.0.0

Repository <https://raeesaganey91.r-universe.dev>

Date/Publication 2026-05-15 14:22:32 UTC

RemoteUrl <https://github.com/raeesaganey91/widerhino>

RemoteRef HEAD

RemoteSha 2df4ee67d3205b8469563318321daeb7e0428d13

Contents

.calibrate.axis	2
axes_coordinates	3
CVAbiplot	3
CVAgsvd	4
get.GSVD	4
sim_data	5
Index	6

<code>.calibrate.axis</code>	<i>Calibrate axis</i>
------------------------------	-----------------------

Description

Calibrate axis

Usage

```
.calibrate.axis(  
  j,  
  Xhat,  
  means,  
  sd,  
  axes.rows,  
  ax.which,  
  ax.tickvec,  
  ax.orthogxvec,  
  ax.orthogyvec  
)
```

Arguments

<code>j</code>	<code>j</code>
<code>Xhat</code>	<code>Xhat</code>
<code>means</code>	<code>means</code>
<code>sd</code>	<code>sd</code>
<code>axes.rows</code>	<code>axes.rows</code>
<code>ax.which</code>	<code>ax.which</code>
<code>ax.tickvec</code>	<code>ax.tickvec</code>
<code>ax.orthogxvec</code>	<code>ax.orthogxvec</code>
<code>ax.orthogyvec</code>	<code>ax.orthogyvec</code>

Value

Calibrated axes

axes_coordinates *Provide axes coordinates*

Description

Provide axes coordinates

Usage

```
axes_coordinates(bp, which.var = 1:bp$p)
```

Arguments

bp	Object
which.var	which variable(s) to find coordinates

Value

Axes coordinates

CVAbiplot *Plot the CVA biplot*

Description

Plot the CVA biplot

Usage

```
CVAbiplot(x, which.var = 1:x$p, var.label = TRUE, group.col = NULL)
```

Arguments

x	Object from CVAgsvd
which.var	which variable to display on the biplot
var.label	whether to display label for variable name
group.col	vector of colours for the groups in the data

Value

A CVA biplot based on the GSVD

Examples

```
data(sim_data)
CVAgsvd(X=sim_data[,2:301],group = sim_data[,1])|>
CVAbiplot(group.col=c("tan1","darkcyan","darkslateblue"),which.var = 1:10)
```

CVAgsvd

CVA using the GSVD

Description

Compute canonical variate analysis using the generalised singular value decomposition when number of variables (p) is larger than the number of samples (n).

Usage

```
CVAgsvd(X, group)
```

Arguments

X	n x p data matrix
group	vector of size n showing the groups

Details

If $p < n$, then the solution defaults to the standard canonical variate analysis.

Value

An object with components of a CVA biplot

Examples

```
CVAgsvd(X=iris[,1:4],group = iris[,5]) |>  
CVAbiplot(group.col = c("orange","red","pink"))
```

get.GSVD*Get GSVD Get the components of the GSVD decomposition*

Description

Get GSVD Get the components of the GSVD decomposition

Usage

```
get.GSVD(A, B)
```

Arguments

A	Matrix A
B	Matrix B

Value

Returns components from the GSVD decomposition

sim_data	<i>Simulated Data</i>
----------	-----------------------

Description

Class Group variable: 0, 1, 2

X1 Variable 1 ...

X300 Variable 300

Format

A data set with 100 rows and 301 columns

Source

simulated data

Index

* datasets

- sim_data, 5
- .calibrate.axis, 2
- axes_coordinates, 3
- CVAbiplot, 3
- CVAgsvd, 4
- get.GSVD, 4
- sim_data, 5